

Elite 4200 Riflescope Specifications

MODEL	FINISH	POWER / OBJ. LENS (mm)	RETICLE	FIELD-OF-VIEW (ft@100yds / m@100m)	WEIGHT (oz / g)	LENGTH (in / mm)	EYE RELIEF (in / mm)	EXIT PUPIL (mm)	CLICK VALUE (in@100yds / mm@100m)	ADJ. RANGE (in@100yds / m@100m)	MNTNG. LENGTH (in / mm)
42-1636M	MATTE	1.5-6 x 36	Multi-X*	61.8/20.6@1.5x / 16.1/5.4@6x	15.4 / 436	12.8 / 325	3.3 / 83	14.6@1.5x / 6@6x	.25 / 7	60 / 1.7	6.0 / 152
42-2104M	MATTE	2.5-10 x 40	Multi-X	41.5/13.8@2.5x / 10.8/3.6@10x	16 / 453	13.5 / 343	3.3 / 83	15.6@2.5x / 4@10x	.25 / 7	50 / 1.4	6.0 / 152
42-2104G	GLOSS	2.5-10 x 40	Multi-X	41.5/13.8@2.5x / 10.8/3.6@10x	16 / 453	13.5 / 343	3.3 / 83	15.6@2.5x / 4@10x	.25 / 7	50 / 1.4	6.0 / 152
42-2104S	SILVER	2.5-10 x 40	Multi-X*	41.5/13.8@2.5x / 10.8/3.6@10x	16 / 453	13.5 / 343	3.3 / 83	15.6@2.5x / 4@10x	.25 / 7	50 / 1.4	6.0 / 152
42-2105M	MATTE	2.5-10 x 50	Multi-X*	40.3/13.4@2.5x / 10.8/3.6@10x	18 / 510	14.3 / 363	3.3 / 83	15@2.5x / 5@10x	.25 / 7	50 / 1.4	5.9 / 149
42-2151M	MATTE	2.5-10 x 50	Illuminated Dot	40/13.3@2.5x / 11/3.7@10x	22 / 624	14.5 / 368	3.3 / 83	5@10x / 15@2.5x	.25 / 7	60 / 1.7	6.5 / 165
42-4164M	MATTE	4-16 x 40	Multi-X*	26/8.7@4x / 7/2.3@16x	18.6 / 526	14.4 / 365	3.5 / 89	10@4x / 25@16x	.125 / 3.5	40 / 1	6.25 / 159
42-4165M	MATTE	4-16 x 50	Multi-X*	26/9@4x / 7/2@16x	22 / 623	15.6 / 396	3.6 / 92	12.5@4x / 3.1@16x	.125 / 3.5	50 / 1.4	5.9 / 149
*42-6242M	MATTE	6-24 x 40	Mil Dot	18/6@6x / 6.0/2@24x	20.2 / 572	16.9 / 429	3.3 / 83	6.7@6x / 1.7@24x	.125 / 3.5	26 / .7	7.9 / 200
*42-6243A	MATTE	6-24 x 40	1/4 M.O.A. Dot	18/6@6x / 6.0/2@24x	20.2 / 572	16.9 / 429	3.3 / 83	6.7@6x / 1.7@24x	.125 / 3.5	26 / .7	7.9 / 200
42-6244M	MATTE	6-24 x 40	Multi-X*	18/4.5@6x / 6.0/2@24x	20.2 / 572	16.9 / 429	3.3 / 83	6.7@6x / 1.7@24x	.125 / 3.5	26 / .7	7.9 / 200
42-8324M	MATTE	8-32 x 40	Multi-X*	14/4.7@8x / 3.75/1.3@32x	22 / 623	18 / 457	3.3 / 83	5@8x / 1.25@32x	.125 / 3.5	20 / .5	8.0 / 203
**42-2146M	MATTE	2.5-10 x 40	FIREFLY™	41.5/13.8@2.5x / 10.8/3.6@10x	16 / 453	13.5 / 343	3.3 / 83	15.6@2.5x / 4@10x	.25 / 7	50 / 1.4	6.0 / 152

Elite 3200 Riflescope Specifications

MODEL	FINISH	POWER / OBJ. LENS (mm)	RETICLE	FIELD-OF-VIEW (ft@100yds / m@100m)	WEIGHT (oz / g)	LENGTH (in / mm)	EYE RELIEF (in / mm)	EXIT PUPIL (mm)	CLICK VALUE (in@100yds / mm@100m)	ADJ. RANGE (in@100yds / m@100m)	MNTNG. LENGTH (in / mm)
32-1040M	MATTE	10 x 40	Mil Dot	11 / 3.7	15.5 / 439	11.7 / 297	3.5 / 89	4.0	.25 / 7	100 / 2.8	6 / 152
32-2632M	MATTE	2-6 x 32	Multi-X*	10/3@2x / 4/1.3@6x	10 / 283	9 / 229	20 / 508	16-5.3	.25 / 7	50 / 1.4	4.0 / 102
32-2632S	SILVER	2-6 x 32	Multi-X*	10/3@2x / 4/1.3@6x	10 / 283	9 / 229	20 / 508	16-5.3	.25 / 7	50 / 1.4	4.0 / 102
32-2732M	MATTE	2-7 x 32	Multi-X*	44.6/15@2x / 12.7/4@7x	12 / 340	11.6 / 295	3.0 / 76	12.2-4.6	.25 / 7	50 / 1.4	6.0 / 152
32-3940G	GLOSS	3-9 x 40	Multi-X*	33.8/11@3x / 11.5/4@9x	13 / 368	12.6 / 320	3.3 / 83	13.3-4.4	.25 / 7	50 / 1.4	6.0 / 152
32-3940S	SILVER	3-9 x 40	Multi-X*	33.8/11@3x / 11.5/4@9x	13 / 368	12.6 / 320	3.3 / 83	13.3-4.4	.25 / 7	50 / 1.4	6.0 / 152
32-3943	MATTE	3-9 x 40	3-2-1 Low Light™	33.8/11@3x / 11.5/4@9x	13 / 368	12.6 / 320	3.3 / 83	13.3-4.4	.25 / 7	50 / 1.4	6.0 / 152
32-3944M	MATTE	3-9 x 40	Multi-X*	33.8/11@3x / 11.5/4@9x	13 / 368	12.6 / 320	3.3 / 83	13.3-4.4	.25 / 7	50 / 1.4	6.0 / 152
32-3953	MATTE	3-9 x 50	3-2-1 Low Light™	31.5/10@3x / 10.5/4@9x	19 / 538	15.7 / 399	3.3 / 83	16-5.6	.25 / 7	50 / 1.4	6.1 / 156
32-3954M	MATTE	3-9 x 50	Multi-X*	31.5/10@3x / 10.5/4@9x	19 / 538	15.7 / 399	3.3 / 83	16-5.6	.25 / 7	50 / 1.4	6.1 / 156
32-3955E	MATTE	3-9 x 50	European	31.5/10@3x / 10.5/4@9x	22 / 623	15.6 / 396	3.3 / 83	16-5.6	.36 / 10	70 / 1.9	6.1 / 156
32-4124A	MATTE	4-12 x 40	Multi-X*	26.9/9@4x / 9/3@12x	15 / 425	13.2 / 335	3.3 / 83	10-3.33	.25 / 7	50 / 1.4	6.0 / 152
32-5154M	MATTE	5-15 x 40	Multi-X*	21/7@5x / 7/2.3@15x	19 / 539	14.5 / 368.3	4.3 / 108	9-2.7	.25 / 7	50 / 1.4	6.0 / 152
32-5155M	MATTE	5-15 x 50	Multi-X*	21/7@5x / 7/2@15x	19 / 539	15.9 / 403	3.4 / 86	10-3.3	.25 / 7	40 / 1.0	5.9 / 149