

KWIK-SITE – WEAVER® BASE MOUNT CHART

Mount Reference Chart for Rifles, Pistols & Shotguns		Detachable Top Mount			Mount Reference Chart for Rifles, Pistols & Shotguns		Detachable Top Mount		
Make & Model of Firearm		Rear Base	Front Base	1-Pc. Base	Make & Model of Firearm		Rear Base	Front Base	1-Pc. Base
ANSCHUTZ					HERTERS				
• Mark 12		16	16	-	• J9		45	46	-
• 54, 54MS, 64, 64MS, 164, 1413, 1422, 1424, 1430, 1432, 1433, 1434, 1522, 1530, 1532, 1534		91	91	-	• U9 BSA Action		28	28	-
• 153 Deluxe		19	19	-	• U9 round receiver		36	35	-
• 1568		61	46	-	Matte		36M	35M	-
Matte		61M	46M	-	Stainless		36S	35S	-
Stainless		61S	46S	-					
AUTO/SEMI-AUTO SHOTGUNS					HIGH-STANDARD				
• Auto shotguns EXCEPT Rem. 11-48, 11-87, 1100, Sportsman 48, 58, Win. 50, Brown. Dbl. Auto, High Stand. Auto		-	-	-	• High-Power		55	46	-
BROWNING					INTERARMS				
• 1885 High Wall (octagon barrel)		11	29	-	• 92 Carbine (replica of Win. 92)		-	-	-
• 22 Auto		-	-	60A	• ATD		-	35	60A
• 243, 308, 22-50, 222, & 222 Magnum (all in Sako Actions)		72	71	-	• Howa		36	35	-
• 52		85	85	-	Matte		36M	35M	-
• A-Bolt, A-Bolt 22		47	47	-	Stainless		36S	35S	-
Matte		47M	47M	-	• Mark X		55	20A	-
Stainless		47S	47S	-	• Mini-Mark X		23	71A	-
• A-Bolt (European Model)		85	85	-					
• Bolt Action, Hi-Power, older models, Mauser Actions		45	46	-	ITHACA				
• BAR, BAR II		54	54	-	• Deerslayer, 37, 87 (12 Ga. only)		-	61	62
• BLR		25	25	-	• LSA-55, LSA-65		61	61	-
• BLR with flat top		28	28	-	Matte		61M	61M	-
• BBR Long and Short Action		47	46	-	Stainless		61S	61S	-
Matte		47M	46M	-	• 49SS, 22		61S	61S	-
Stainless		47S	46S	-	• Lightning X5		39	39	-
• Buck Mark (pistol)		-	-	-					
BENELLI					JAPANESE				
• With flat surface - See OCTAGON BARRELS		-	-	-	• 6.5mm, 7.7mm		-	-	70
BRITISH 303 w/Enfield Action					KRAG				
• (Use TO-1 Tip Off* Mount Base with Tip-Off* Rings)		-	-	-	• (Offset to left for easy ejection)		-	-	-
BSA					LAKEFIELD				
• Monarch Medium Action 222, 243, 308		36	40A	97	• Mark I, II, 64B		-	-	-
Stainless		36S	40A-S	-	LEE-ENFIELD				
• CF2, Monarch Long Action 7mm, 270, 300-6		36	35	98	• (Use TO-1 Tip-Off Mount Base)		-	-	-
Matte		36M	35M	-	LLAMA (PISTOL)				
Stainless		36S	35S	-	• Super Comanche (flat surface) See OCTAGON BARRELS		-	-	-
• Other High Powers		28	28	-	LONE EAGLE (PISTOL)				
CARCANO					• SSP 91		16	16	-
• Carcano		-	-	-	MARLIN				
CHURCHILL					• 9, 45, 30AS, 36, 62, 93, 336, 336C, 375, 444, 1993, 1894, 1895, Glenfield 30, Zane Grey, Camp-9 Carbine, 922M, 989, 22 Auto Rifle		-	-	63B
• Highlander		-	36	35	• A1, 50		15	15	-
Matte		-	36M	35M	• 39A, 39D, Century octagon bbl.		28	31	90
Stainless		-	36S	35S	• 39A round bbl.		29	16	-
CIL					• 57 Magnum		-	-	58
• 830		-	-	-	• 88, 89, 98		18	18	-
• 871		-	-	62	• 80, 81, 980		12	21	-
• 900		19	19	-	• 455		45	46	-
• 950, 950-C		61	46	-	• 512 Slug Master Matte		-	-	-
Matte		61M	46M	-	• 55 Matte		-	-	-
Stainless		61S	46S	-	• 60, 60SS, 99OL, 70HL, 70P 995, 882L, 882, 25MN, 883, 883N, 883SS, 880, 881		-	-	-
• 972-C		45	46	-	MAUSER including FN, HVA, & Swedish				
COLT					• With Receiver Ring about 1.410" Diameter		45	46	-
• 57		45	46	-	• With Receiver Ring about 1.300" Diameter		55	46	-
• Coltsman in 223, 243, 308 cal. (round rec.)		25	25	-	• Bauer		68	46	-
• Coltsman in 264, 30-06 cal. (round rec.)		54	54	-	• Mark X		55	20A	-
• Coltsman in 223 (Sako action)		67	65	-	MODERN MUZZLE LOADING				
• Coltsman in other calibers (Sako action)		67	65	-	• Knight MK-85, BK-92 (flat rec.)		61	61	-
• Sauer		35	35	-	Matte		61M	61M	-
Matte		35M	35M	-	Stainless		61S	61S	-
Stainless		35S	35S	-	• LK-93, Wolverine, Legend (round rec.)		45	45	-
• H Bar		-	-	-	MOSSBERG				
COOY					• 25, 26, 42, 46M, 140, 142, 146. Also late models 45-46 with 3/4" dia. bbls.		12	13	-
• 60, 600		-	-	-	• 40		16	21	-
• 71		47	46	-	• 43, 44, 144, 46BT, 35. Also early models 45, 46, 46A, 46B with 13/16" dia. bbls.		12	16	-
Matte		47M	46M	-	• 320, 340, 342, 620		21	21	-
Stainless		47S	46S	-	• 640		-	-	63B
CVA					• 680		55	55	-
• Apollo, Stalker		61A	61A	-	• 50, 51, 151, 152, 350, 352		12	12	-
ENFIELD receiver cut down like:					• 400		20A	42	-
• Remington 30		11	11	-	• 472, 479, 679		-	-	80
• Winchester 70		47	46	-	• 500AS, 600 shotguns		-	-	88
Matte		47M	46M	-	• 800		55	55	-
Stainless		47S	46S	-	• 810, RM7		25	11	-
• Remington 721		36	35	-	• 835		-	-	88A
Matte		36M	35M	-	• 1500, 1700		36	35	-
Stainless		36S	35S	-	Matte		36M	35M	-
GARCIA					Stainless		36S	35S	-
• 73		-	-	53	MUSGRAVE				
• 74		67	65	-	• Mark I, Mark II		54	46	-
GOLDEN EAGLE					• Mark III, Mark IV		45	46	-
• 7000		71	71	-	NEW ENGLAND FIREARMS				
H & R					• Handy Rifle, Hornet (use Extra High rings)		-	-	82
• 65, 165, 150, 151 (Auto)		18	18	-	• N.E.F. 10 Ga. Shotgun		19	19	-
• 176		18	16	83	NEW HAVEN				
• 250, 251, 264, 265, 365, 450, 550		45	46	-	• 495B Matte		-	-	-
• 155, SB2 Ultra (22-250)		83	84	-	NORINCO				
• 300, 301, 330, 370 before '73		11	11	-	• 22 Auto (replica of Browning .22 auto)		-	-	60A
• 300, 300 Short Action for '73 and after (22-250, 243, 308)		67	65	-	• JW-15		-	-	-
• 300, 301 Long Action for '73 and after (270, 3006, 7mm, 300 Winchester)		54	46	-	OCTAGON BARRELS OR FLAT TOP RECEIVER				
• 317, 322		11	35	-	Can be fitted with the following flat bases:				
• 317 before the 1975 model		67	65	-	• #50 - (4.500" long, .200/.232 thick) NOTE: #50 can be used with Top Mount Rings on double & single barrel shotguns with ribs thick enough for base screws.				
• 360, 361		-	-	81	• #61 - (1.168" long, .360" thick)				
• 700		-	-	87A	• #63B - (5.450" long, .370" thick)				
• 755, 765, 852, 865		17	21	-	PARKER-HALE				
• 800		12	12	-	• 1000, 1000C, 1100, 1200, 1700		45	46	-
• Topper 30, 22 Jet, 158 before, '73		-	-	60A	• 2600		71	85	-
• Topper 158C for '73 & after, 157 drilled tapped, 058		-	-	82	• Midland		71	75	-

KWIK-SITE – WEAVER® BASE MOUNT CHART

Mount Reference Chart for Rifles, Pistols & Shotguns Make & Model of Firearm	Detachable Top Mount		
	Rear Base	Front Base	1-Pc. Base
PUMP SHOTGUNS			
• Pump shotguns EXCEPT Winchester 42	-	-	-
REMINGTON			
• 700 & 78 Long Action in, 270, 280, 25-06, 7mm Mag., 300 Win. Mag, 264, 375, 458, 40X-L, 721, 725 in 270, 280, 30-06, 375			
Matte	36	35	98
Stainless	36M 36S	35M 35S	-
• 700 & 78 Short Action in 17, 222, 222 Mag., 22-250, 243, 6mm, 308; 722: 40X-S; 725 in 222, 243, 244	36	40A	97
Stainless	36S	40A-S	62
• 740, 742, 760	-	-	70
• 7, 600, 660, XP-100 (70 Base has shim to fill a 1/4" gap)	-	-	93
• 788	76	75	-
• 4, 6, 74, 76, 7400, 7600	-	-	-
• 8, 81	-	-	-
• 10, 11, 12, 510, 511, 521T	43	42	-
• 34, 341	43	42	-
• 12A, 121 with 3/4" diameter barrels	18	13	-
• 121 with 13/16" diameter barrels	18	17	-
• 12C octagon barrel	18	31	-
• 14, 141	20A	27	-
• 41	17	17	-
• 24, 241	-	-	60A
• 25	18	21	-
• 30, 720	11	11	-
• 33	17	13	-
• 513S, 513T	43	44	-
• 514	16	21	-
• 514 (if not drilled and tapped), 550	12	12	-
• 541S, 541T	15	15	-
• 522 Viper	-	-	-
• 552, 572, 581	-	-	-
• Auto 11-48, 1100, Sportsman 48, 58, Win. 50 High Standard Auto (Shotguns)	-	-	-
ROSSI			
• Brazilian revolver with flat surfaced barrel- See OCTAGON BARRELS	-	-	-
RUGER			
(See Pistol Mount™ Systems for Ruger Mini-14)			
• 1	85	89	-
• 3	85	86	-
• 10/22	-	-	T0-9
Stainless	-	-	T0-9S
• M44	47	68	-
• M77 (round top)	79	35	-
• M77 (with integral mount)	-	-	-
Stainless	-	-	-
• 77/22, Mini-14 Ranch & Mini-30 (w/ integral mount)	-	-	-
Stainless	-	-	-
• Mini-14 See PISTOL MOUNT™ SYSTEMS	-	-	-
• Mark II, Pistol All Models - See PISTOL MOUNT™ SYSTEMS	-	-	-
SAKO			
• 72, 75, 78	85	85	-
• Finnwolf	-	-	53
• Forester Finnebear, Vixen	67	65	-
• Whitetail Hunter	61	61	-
Matte	61M	61M	-
Stainless	61S	61S	-
SAUER			
• 200	35	35	-
Matte	35M	35M	-
Stainless	35S	35S	-
SAVAGE			
• 3	16	21	-
• 4, 5	12	13	-
• 6, 7	12	12	-
• 29 (round bbl.)	11	22	-
• 19, 23	15	16	-
• 20, 340, 340E, 342, 840, 842E	-	-	-
• 24	-	-	74
• 24 (grooved receiver)	-	-	-
• 25 octagon bbl.	19	31	-
• 40, 45	11	11	-
• 57	-	-	93
• 99, 189S, 1899	14	19	-
• 170	-	-	62
• 219	12	30	-
• T10 (E & S), 111, 112 (R, V, & FV), 116FSS	61	46	-
Matte	61M	46M	-
Stainless	61S	46S	-
• 402 EXTENSION BASE (can use instead of 46 Base if more/less space or eye relief is required)	61	402	-
• 2400	67	65	-
SCHULTZ & LARSEN			
• Schultz & Larsen	54	46	-
SEARS			
• 50, 51	45	46	-
• 51L	55	46	-
• 53	47	46	-
Matte	47M	46M	-
Stainless	47S	46S	-
• 54, 100	-	-	-
SHILLEN			
• Flat top receiver	61	61	-
Matte	61M	61M	-
Stainless	61S	61S	-
• Round receiver	35	35	-
Matte	35M	35M	-
Stainless	35S	35S	-
SMITH & WESSON			
• Mauser actions with small receiver ring	55	46	-
• 1500, 1600, 1700	36	35	-
Matte	36M	35M	-
Stainless	36S	35S	-
• L, K, & N Frame Revolvers (factory drilled & tapped)	-	-	401
Stainless	-	-	401S
• 41	-	-	62
• 2206 TGT (factory drilled & tapped) Stainless	-	-	407S

Mount Reference Chart for Rifles, Pistols & Shotguns Make & Model of Firearm	Detachable Top Mount		
	Rear Base	Front Base	1-Pc. Base
SPRINGFIELD			
• 03	54	55	-
• 03-A3	59	45	-
SPRINGFIELD ARMOY			
• 1911 A-2 SASS Conversion	-	-	26
STEVENS			
• 26	22	22	-
• 27 octagon	31	31	-
• 53	16	21	-
• 56, 66	12	13	-
• 57, 76, 417-1/2, 762	12	12	-
• 110E	61	46	-
Matte	61M	46M	-
Stainless	61S	46S	-
• 322, 325	-	-	-
• 416	18	17	-
• 417	15	15	-
• 418, 418-1/2	16	16	-
STEVENS-SPRINGFIELD			
• 83	16	21	-
• 85, 87, 872	12	12	-
• 840	-	-	-
THOMPSON/CENTER			
• Contender Handgun, Carbine	-	-	92A
Stainless	-	-	92AS
• Scout (Rifle & Pistol)	-	-	404
• TCR	-	-	405
• ThunderHawk, Fire Hawk	406	406	-
Stainless	406S	406S	-
• Trad. Style Muzzleloaders (Universal Adaptor)	-	-	408
TIKKA			
• Tikka (flat receiver)	61	61	-
TRADITIONS			
• Whitetail	61A	61A	-
• In-Line Buckhunter (50 cal.)	75	75	-
U.S. CARBINE			
• Cal. 30 M1 (not factory drilled & tapped - requires 4 holes in receiver & relief space cut in stock to accommodate base)	-	-	-
VALMET			
• Tapered Dovetail, Sako Design	66	67	-
VOERE			
• 2130	28	28	-
• 2150, 2165/1, 2165/2, 2165/3, 2165/4	45	46	-
WEATHERBY			
• Mark V, Vanguard	36	35	-
Matte	36M	35M	-
Stainless	36S	35S	-
• Mark V 22-250, 224	36	46	-
Matte	36M	46M	-
Stainless	36S	46S	-
• Other models with FN Mauser actions	45	46	-
WESTERN FIELD			
• 712	-	-	-
• 730	25	11	-
• 740	-	-	63B
• 750	67	65	-
• 770	55	20A	-
• 772	-	-	80
• 775, 780	55	55	-
WHITE			
• All Receivers	35	11	-
WINCHESTER			
(Including Ranger Models)			
• 03, 63	19	22	-
• 06, 62, 62A, 90 octagon bbl.	32	32	-
• 05, 07, 10	20A	17	-
• 42	-	-	-
• 43	18	18	-
• 52 (hole spacing different)	25	57	-
• 52 after 1993 (if hole spacing same)	46	46	-
Matte	46M	46M	-
Stainless	46S	46S	-
• 53, 55, 64, 65, 66, 71, 86, 92, 95	48	46	-
• 54, Early Model 70 (Below Serial #66, 350)	12	13	-
• 57, 69	21	21	-
• 60, 67, 68	19	13	-
• 61 round bbl.	25	37	-
• 61 octagon bbl.	19	17	-
• 69A, 72, 47	12	17	-
• 70 Long Action (hole spacing same)	47	46	96
Matte	47M	46M	-
Stainless	47S	46S	-
• 70 Long Action (hole spacing different)	49A	46	-
• 70 Short Action	47	46	99
Matte	47M	46M	-
Stainless	47S	46S	-
• 74	12	12	-
• 75 Sporter	15	30	-
• 75 Target	15	16	-
• 77	15	32	-
• 88, 100	-	-	53
• 94 pre-1964	-	-	-
• 94 after 1964	-	-	-
• 94 Big Bore 375	-	-	-
• 94 Angle-Eject Big Bore	95	403	-
• 94 Angle-Eject (except earliest models)	95	94	-
• 94/22	-	-	T0-10
• 520	85	85	-
• 670, 770	47	46	-
Matte	47M	46M	-
Stainless	47S	46S	-
• 777	71	71	-
• 1300 shotgun	46	46	-
ZB			
• 22	28	24	-
• Hornet, 218 Bee	39	24	-