

WEAVER™ MOUNT APPLICATIONS CHART		N O T E S	WEAVER™ ALUMINUM TOP MOUNT BASES						MULTI-SLOT BASES			STEEL LOCK SEE-THRU RINGS	Complete Mount Systems	SIDE MOUNT	GRAND SLAM™ STEEL TOP MOUNT BASES				GRAND SLAM™ DOVETAIL BASES	
Revision K: 10/13/25	MAKE		MODEL OF FIREARM COLOR INDICATES FINISH: BLACK MATTE SILVER Yellow Shading = Inactive	STANDARD 2-PC BASES			EXTENSION BASES		1-PC	1-PC	1-PC	No Bases Required	Bases w/Rings	USE ONLY WITH SIDE MT BRACKET	STANDARD		EXTENSION		1-PC	2-PC
				REAR	FRONT	Base Pairs	REAR	FRONT	1-PC	Multi-Slot Bases	Extended multi-slot bases				Extended multi- slot bases 20 MOA	REAR	FRONT	REAR		
SAUER	200			35 (48035)	35 (48035)			40A (48040)												
SAUER	- Matte			35M (48500)	35M (48500)			40AM (48428)							S35 (48224)	S35 (48224)				
SAUER	- Silver			35S (48006)	35S (48006)															
SAUER	SHR 970			25 (48025)	25 (48025)															
SAVAGE	A17, A22 Mag, A22 (Post Dec 2020 or all serial #'s after 3380376)			46 (48046)	46 (48046)	48478		402 (48108)	402 (48108)											
SAVAGE	- Matte			46M (48502)	46M (48502)	48466		402M (48429)	402M (48429)		48308									
SAVAGE	- Silver			46S (48004)	46S (48004)			402S (48430)	402S (48430)											
SAVAGE	A22 (Pre Dec 2020 or all serial #'s below 3380376)			46 (48046)	46 (48046)	48478		402 (48108)	402 (48108)											
SAVAGE	- Matte			46M (48502)	46M (48502)	48466		402M (48429)	402M (48429)		48307									
SAVAGE	- Silver			46S (48004)	46S (48004)			402S (48430)	402S (48430)											
SAVAGE	Rascal										48302									
SAVAGE	Axis Series, Edge Pre- June 2021 6-48 Screws			46 (48046)	46 (48046)			402 (48108)	402 (48108)											
SAVAGE	- Matte			46M (48502)	46M (48502)	48466		402M (48429)	402M (48429)		506 (48347)	99487	99488	(20MOA)	S46 (48227)	S46 (48227)	S402 (48247)	S402 (48247)		
SAVAGE	- Silver			46S (48004)	46S (48004)			402S (48430)	402S (48430)											
SAVAGE	Axis Series, Post- June 2021 8-40 Screws	29		653 (48420)	653 (48420)	48489		654 (48421)	654 (48421)		48400	99610	99611	(20 MOA)	S670 (48260)	S670 (48260)	S671 (48261)	S671 (48261)		
SAVAGE	3			16 (48016)											2 (48402)					
SAVAGE	4, 5			12 (48012)	13 (48013)										2 (48402)					
SAVAGE	6, 7			12 (48012)	12 (48012)										2 (48402)					
SAVAGE	29 (Round Barrel)			11 (48011)																
SAVAGE	19, 23			15 (48015)	16 (48016)										2 (48402)					
SAVAGE	20, 340, 340E, 342, 840, 842E	14													1 (48401)					
SAVAGE	320									417M (48440)	417T (48333)									
SAVAGE	24	17								74 (48074)										
SAVAGE	25 varmint			16 (48016)	16 (48016)															
SAVAGE	25 (Octagon Barrel)			19 (48019)																
SAVAGE	40 & 45 Super Sporter			11 (48011)	11 (48011)										2 (48402)					
SAVAGE	67 Shotgun									93 (48093)										
SAVAGE	93F Heavy Barrel, 93, 93FVSS	5,26		16 (48016)	16 (48016)															
SAVAGE	99, 1895, 1899	5,26		14 (48014)	19 (48019)															
SAVAGE	170																			
SAVAGE	212 (Shot Gun)	5,25		46 (48046)	46 (48046)			402 (48108)	402 (48108)											
SAVAGE	- Matte			46M (48502)	46M (48502)			402M (48429)	402M (48429)		413T (48329)	99489	99490	(20MOA)	S46 (48227)	S46 (48227)	S402 (48247)	S402 (48247)		
SAVAGE	219			12 (48012)	30 (48030)										2 (48402)					
SAVAGE	220 (Shot Gun)	5,25		46 (48046)	46 (48046)			402 (48108)	402 (48108)											
SAVAGE	- Matte			46M (48502)	46M (48502)			402M (48429)	402M (48429)		413T (48329)	99489	99490	(20MOA)	S46 (48227)	S46 (48227)	S402 (48247)	S402 (48247)		
SAVAGE	Renegade (Shot Gun)																			
SAVAGE	- Matte									93A (48506)	93AT (48339)									
SAVAGE	10, 11, 12, 14 & 16 (Short Actions), Striker Pstl, 510, 512, 516, S/A 10 ML (2-piece ONLY) Pre 2003 Models	22		61 (48061)	46 (48046)			402 (48108)	420M (48438)											
SAVAGE	- Matte			61M (48504)	46M (48502)	48465		402M (48429)	402M (48429)						S61 (48234)	S46 (48227)		S402 (48247)		
SAVAGE	- Silver			61S (48002)	46S (48004)			402S (48430)												
SAVAGE	110, 111, 112, 114, 116 (Long Actions); 210 Shtg (use X-high rings) Pre 2003 Models	22		61 (48061)	46 (48046)			402 (48108)	413 (48425)						1 (48401)					
SAVAGE	- Matte			61M (48504)	46M (48502)	48465		402M (48429)	413M (48442)						S61 (48234)	S46 (48227)		S402 (48247)		

Date 10/13/2025
Revision K

NOTES

1	Shimming is probably required for perfect scope alignment.
2	Rear base may require modifications for correct fit to military actions.
3	Front base may require modification for correct fit.
4	Gun will have to be drilled and tapped.
5	Front base screws must be shortened by grinding.
6	May require bolt and/or safety alteration, otherwise firearm cannot function safely and properly. Consult with a qualified gunsmith.
7	Base DOES NOT FIT Rossi Large Frame Matched Pair Combos. (All models with 12 GA or 20 GA barrels.)
8	Remove rear sight to use.
9	The handiest way to pinpoint the correct base for the Win. 52 & Win. 70 Long action Rifles is to check the spacing of the tapped holes for the rear base and compare it to the hole spacing for the front base. Does it have: HOLE SPACING THE SAME: Model 52: use 46+ 46, Model 70: use 47+ 46 HOLE SPACING DIFFERENT: Model 52: use 25+ 57 Model 70: use 49A+ 46
10	The Weaver type base built into this rifle will accept Weaver rings but our highest ring (1" See-Thru #49513) still isn't high enough to clear the front sight.
11	The Weaver type base built into this firearm will accept any Detachable Top Mount Weaver Ring.
12	All 22 Rifles that have Grooved Receiver with 3/8" Dovetail for Tip-Off Rings.(49819 & 49515)
13	Ruger Mark II Pistols. Weaver only offers a clamp on base with 1" rings (Pistol Mount System #306). Ruger supplies a short or long base and 1" or 30mm rings w/factory drilled and tapped pistols. Contact Ruger at 602-778-6555 for these items.
14	Bolt Clearance problem may exist and scope will not be centered.
15	Base accepts Tip-Off Rings only.
16	TO-9, TO-10 & TO-11 bases accept either Detachable Top Mount Rings or Tip-Off Rings. Each have crossbolt slots and 3/8" grooves for both applications.
17	Must be factory drilled and tapped.
18	One-Piece base attaches to barrel and extends back over receiver.
19	Requires the use of Thompson/Center base adapter.
20	Requires drilling and tapping 4 holes in receiver and relief space cut in stock to clear base.
21	Rear base is positioned on top of receiver and front base is positioned on the barrel. Drilling & tapping required. One-piece base mounts w/2 set screws & newer guns are factory drilled & tapped.
22	For shorter tube scopes or red dot scopes use #402 extension front base or one-piece base if available. Extension base allows an extra .689".
23	WARNING: NOT FOR USE WITH X-FRAME REVOLVERS. USE ON FIREARMS OTHER THAN THOSE LISTED ABOVE MAY CAUSE INJURY.
24	Top mount base is designed to fit 12GA models only.
25	Can be used with Tactical Multi Slot Bases.
26	Rear Base Screws must be shortened by grinding.
27	Not available or discontinued.
28	Tactical Extended Multi-Slot Bases have 20 MOA versions as well.
29	Savage changed the Axis receiver threads from 6-49 to 8-40 in June of 2021. To identify what threads, Savage Arms added a drill point on the receiver. The drill point is located on the left side of the ejection port. If there is a drill point then the receiver has 8-40 threads, if no drill point, then the receiver has 6-48 threads.